



Norcros SA: TAL Contact adhesive

TAL CONTACT ADHESIVE®



DESCRIPTION

TAL CONTACT ADHESIVE is a polychloroprene-based contact adhesive designed to be particularly easy to use. For this reason it has a high viscosity and an exceptionally long tack life.

AREAS OF APPLICATION

TAL CONTACT ADHESIVE is suitable for the bonding of wood, metal, rubber, leather, melamine laminate and ceramic materials.

TECHNICAL DATA

Specific Gravity	0.87
Flash Point	-18°C

DIRECTIONS

TAL CONTACT ADHESIVE is specifically designed for two-way dry application. Firstly, the surface to be bonded should be thoroughly cleaned and the adhesive stirred. The adhesive should then be applied to both surfaces and allowed to dry completely, normally 10 minutes. The bond can now be made at any time during the next 60 minutes, or longer on non-porous substrates. It is advisable to get as much pressure as possible at this stage to make good contact.

STORAGE AND SHELF LIFE

When stored under cover between 5°C and 30°C, the product has a shelf life of 6 months.

PACKAGING

TAL CONTACT ADHESIVE is available in 1L, 5L and 25L tins.

WARNING

FLAMMABLE • DO NOT INGEST • USE ONLY AS DIRECTED • WEAR PROTECTIVE GLOVES AND GOGGLES • WORK IN A WELL VENTILATED AREA • DO NOT INHALE SOLVENTS

TAL GUARANTEE

TAL products are manufactured to the highest standards and are guaranteed to be free from manufacturing defects and fit for design purpose. TAL products must be used strictly in accordance with TAL's methods and materials specifications and good working practice.



Another successful installation guaranteed

A NORCROS COMPANY

Solutions Through Technology



TAL CONTACT ADHESIVE®



DESCRIPTION

TAL CONTACT ADHESIVE is a polychloroprene-based contact adhesive designed to be particularly easy to use. For this reason it has a high viscosity and an exceptionally long tack life.

AREAS OF APPLICATION

TAL CONTACT ADHESIVE is suitable for the bonding of wood, metal, rubber, leather, melamine laminate and ceramic materials.

TECHNICAL DATA

Specific Gravity	0.87
Flash Point	-18°C

DIRECTIONS

TAL CONTACT ADHESIVE is specifically designed for two-way dry application. Firstly, the surface to be bonded should be thoroughly cleaned and the adhesive stirred. The adhesive should then be applied to both surfaces and allowed to dry completely, normally 10 minutes. The bond can now be made at any time during the next 60 minutes, or longer on non-porous substrates. It is advisable to get as much pressure as possible at this stage to make good contact.

STORAGE AND SHELF LIFE

When stored under cover between 5°C and 30°C, the product has a shelf life of 6 months.

PACKAGING

TAL CONTACT ADHESIVE is available in 1ℓ, 5ℓ and 25ℓ tins.

WARNING

FLAMMABLE • DO NOT INGEST • USE ONLY AS DIRECTED • WEAR PROTECTIVE GLOVES AND GOGGLES • WORK IN A WELL VENTILATED AREA • DO NOT INHALE SOLVENTS

TAL GUARANTEE

TAL products are manufactured to the highest standards and are guaranteed to be free from manufacturing defects and fit for design purpose. TAL products must be used strictly in accordance with TAL's methods and materials specifications and good working practice.



Another successful installation guaranteed

A **NORCROS** COMPANY



Solutions Through Technology

TAL CONTACT ADHESIVE®

TAL TECHNICAL ADVISORY SERVICE

For a detailed methods and materials specification contact the TAL TECHNICAL ADVICE CENTRE on our toll free line on 0800 008 008 or fax (011) 316 3127.

PRECAUTIONS

TAL CONTACT ADHESIVE is highly inflammable.

IMPORTANT NOTICE

Contact TAL for further health and safety information. Dispose of this product in accordance with local regulations. The obligation of TAL (Pty) Ltd shall be to replace any of this product proved to be defective in any way.

CONTACT DETAILS

Toll free Technical helpline 0800 008 008

Johannesburg: (011) 316 3133 • Cape Town (021) 386 1810 • Durban (031) 700 1535

TAL reserves the right to change the information on this datasheet.

Another successful installation guaranteed