



Norcros SA: TAL epoxy cleaning fluid/gel

TAL EPOXY CLEANING FLUID/GEL®



DESCRIPTION

A blend of solvents specifically designed to clean off TAL EPOXY GROUT residues from the surface of tiles after the grouting operation. These products are non-flammable.

APPLICATION

The TAL EPOXY CLEANING FLUID is a thickened version of TAL EPOXY CLEANING GEL. It was specifically developed for use on walls where run-off would be experienced, but is also useful for cleaning large/stubborn deposits. The cleaners should be applied by cloth (flat) or brush.

The solvents contained in these products dissolve many materials so that wax/polish, butter/margarine, fats/oils plus ready-mixed tile adhesive pastes and priming and bonding agents (TAL KEYCOAT and TAL BOND) will be dissolved off with the cleaners. When cleaning epoxy residues, this should be carried out as soon after application as possible – uncured epoxy is significantly easier to remove.

COVERAGE

Coverage varies considerably, depending on severity of contamination.

STORAGE AND SHELF LIFE

The solvents in these products are highly volatile. The bottles should therefore be stored under cover, away from sources of heat and direct sunlight (between 5°C and 25°C).

PACKAGING

TAL EPOXY CLEANING FLUID and TAL EPOXY CLEANING GEL are both available in 5L and 1L plastic bottles.

WARNING

DO NOT INGEST • USE ONLY AS DIRECTED • WEAR PROTECTIVE GLOVES AND GOGGLES • WORK IN A WELL VENTILATED AREA.

NOTE

Do not expose containers to temperatures exceeding 38°C. The solvents irritate the skin – rubber gloves should be worn. Do not use in confined areas, especially for extended periods. The solvents have an anaesthetic effect.

TAL GUARANTEE

TAL products are manufactured to the highest standards and are guaranteed to be free from manufacturing defects and fit for design purpose. TAL products must be used strictly in accordance with TAL's methods and materials specifications and good working practice.

TAL TECHNICAL ADVISORY SERVICE

For a detailed methods and materials specification contact the TAL TECHNICAL ADVICE CENTRE on our toll free line on 0800 008 008 or fax (011) 316 3127

CONTACT DETAILS

Toll free Technical helpline 0800 008 008
Johannesburg: (011) 316 3133 • Cape Town (021) 386 1810 • Durban (031) 700 1535

TAL reserves the right to change the information on this datasheet.



Another successful installation guaranteed

an INFIXION MEDIA COMPANY

Solutions Through Technology



- ❖ [Go to Specifile](#)
- ❖ [Click here to view supplier details](#)
- ❖ [See full brochure](#)

TAL EPOXY CLEANING FLUID/GEL®



DESCRIPTION

A blend of solvents specifically designed to clean off TAL EPOXY GROUT residues from the surface of tiles after the grouting operation. These products are non-flammable.

APPLICATION

The TAL EPOXY CLEANING GEL is a thickened version of TAL EPOXY CLEANING FLUID. It was specifically developed for use on walls where run-off would be experienced, but is also useful for cleaning large/stubborn deposits. The cleaners should be applied by cloth (fluid) or brush.

The solvents contained in these products dissolve many materials so that wax/polish, butter/margarine, fats/oils plus ready-mixed tile adhesive pastes and priming and bonding agents (TAL KEYCOAT and TAL BOND) will be dissolved off with the cleaners. When cleaning epoxy residues, this should be carried out as soon after application as possible – uncured epoxy is significantly easier to remove.

COVERAGE

Coverage varies considerably, depending on severity of contamination.

STORAGE AND SHELF LIFE

The solvents in these products are highly volatile. The bottles should therefore be stored under cover, away from sources of heat and direct sunlight (between 5°C and 25°C).

PACKAGING

TAL EPOXY CLEANING FLUID and TAL EPOXY CLEANING GEL are both available in 5ℓ and 1ℓ plastic bottles.

WARNING

DO NOT INGEST • USE ONLY AS DIRECTED • WEAR PROTECTIVE GLOVES AND GOGGLES • WORK IN A WELL VENTILATED AREA.

NOTE

Do not expose containers to temperatures exceeding 38°C. The solvents irritate the skin – rubber gloves should be worn. Do not use in confined areas, especially for extended periods. The solvents have an anaesthetic effect.

TAL GUARANTEE

TAL products are manufactured to the highest standards and are guaranteed to be free from manufacturing defects and fit for design purpose. TAL products must be used strictly in accordance with TAL's methods and materials specifications and good working practice.

TAL TECHNICAL ADVISORY SERVICE

For a detailed methods and materials specification contact the TAL TECHNICAL ADVICE CENTRE on our toll free line on 0800 008 008 or fax (011) 316 3127

CONTACT DETAILS

Toll free Technical helpline 0800 008 008
Johannesburg: (011) 316 3133 • Cape Town (021) 386 1810 • Durban (031) 700 1535

TAL reserves the right to change the information on this datasheet.



Another successful installation guaranteed

A **MORCHOS** COMPANY



Solutions Through Technology