



Norcros SA: TAL goldstar 2

- ❖ [Go to Specifile](#)
- ❖ [Click here to view supplier details](#)
- ❖ [See full brochure](#)

TAL GOLDSTAR 2®



DESCRIPTION

TAL GOLDSTAR 2 is an ultra fast setting adhesive. It is a cement based powder adhesive for fixing ceramic tiles to walls and floors. TAL GOLDSTAR 2 is ideal for small repair jobs, tile fixing in doorways and passages, where access is required soon after tiling. The adhesive may be used in interior and exterior conditions. Exterior applications require the use of TAL BOND instead of water.

TECHNICAL DATA

TAL GOLDSTAR 2 can be mixed with either clean water or used with TAL BOND for special applications.

Mix ratio	4 : 1	4 : 1
Pot Life	20 - 30 minutes	20 - 30 minutes
Open Times	10 minutes	10 minutes
Application Temperature Range	+ 5°C to + 30°C	+ 5°C to + 30°C
Crouching After	1 hour	1 hour
Full Service	2 hour	2 hour
Flexibility	Poor	Good
Temperature Resistance	0°C to + 100°C	- 30°C to + 100°C
Ageing	Excellent	Excellent
Resistance to Damp	Good	Excellent
Tensile Strength (24 Hours)	> 0.5N/mm ²	> 1.0N/mm ²

DIRECTIONS

Using a notched TAL FLOOR TROWEL (which will give a solid bed of adhesive 3 - 4mm thick) 20kg will cover approximately 4m². Using a notched TAL WALL TROWEL (which will give a ribbed cover with ± 60% coverage ± 3mm thick) 20kg will cover approximately 7m².

STORAGE AND SHELF LIFE

When stored in dry conditions, under cover between 5°C and 30°C, the product has a shelf life of 6 months.

PACKAGING

20kg bags

WARNING

DO NOT INGEST • USE ONLY AS DIRECTED • WEAR PROTECTIVE GLOVES AND GOGGLES • USE A SUITABLE DUST MASK.
• WORK IN A WELL VENTILATED AREA.

TAL GUARANTEE

TAL products are manufactured to the highest standards and are guaranteed to be free from manufacturing defects and fit for design purpose. TAL products must be used strictly in accordance with TAL's methods and materials specifications and good working practice.



Solutions Through Technology

DESCRIPTION

TAL GOLDSTAR 2 is an ultra fast setting adhesive. It is a cement based powder adhesive for fixing ceramic tiles to walls and floors. TAL GOLDSTAR 2 is ideal for small repair jobs, tile fixing in doorways and passages, where access is required soon after tiling. The adhesive may be used in interior and exterior conditions. Exterior applications require the use of TAL BOND instead of water.

TECHNICAL DATA

TAL GOLDSTAR 2 can be mixed with either clean water or used with TAL BOND for special applications.

Mix ratio	4 : 1	4 : 1
Pot Life	20 - 30 minutes	20 - 30 minutes
Open Times	10 minutes	10 minutes
Application Temperature Range	+ 5°C to + 30°C	+ 5°C to + 30°C
Grouting After	1 hour	1 hour
Full Service	2 hour	2 hour
Flexibility	Poor	Good
Temperature Resistance	0°C to + 100°C	- 30°C to + 100°C
Ageing	Excellent	Excellent
Resistance to Damp	Good	Excellent
Tensile Strength (24 Hours)	> 0.5N/mm ²	> 1.0N/mm ²

DIRECTIONS

Using a notched TAL FLOOR TROWEL (which will give a solid bed of adhesive 3 - 4mm thick) 20kg will cover approximately 4m². Using a notched TAL WALL TROWEL (which will give a ribbed cover with ± 60% coverage ± 3mm thick) 20kg will cover approximately 7m².

STORAGE AND SHELF LIFE

When stored in dry conditions, under cover between 5°C and 30°C, the product has a shelf life of 6 months.

PACKAGING

20kg bags

WARNING

DO NOT INGEST • USE ONLY AS DIRECTED • WEAR PROTECTIVE GLOVES AND GOGGLES • USE A SUITABLE DUST MASK.
• WORK IN A WELL VENTILATED AREA.

TAL GUARANTEE

TAL products are manufactured to the highest standards and are guaranteed to be free from manufacturing defects and fit for design purpose. TAL products must be used strictly in accordance with TAL's methods and materials specifications and good working practice.



1 Add 20kg Goldstar 2 to 5l clean, cool water.



2 Mix well while adding powder.



3 Apply adhesive.



4 Bed tiles.



5 Grout after 1 hour.



6 Clean off excess grout.

Another successful installation guaranteed

A **NORCROS** COMPANY



TAL GOLDSTAR 2®

TAL TECHNICAL ADVISORY SERVICE

For a detailed methods and materials specification contact the TAL TECHNICAL ADVICE CENTRE on our toll free line on 0800 008 008 or fax (011) 316 3127.

PRECAUTIONS

TAL GOLDSTAR 2 is non-flammable and is not hazardous to health. Sensitive skin should be protected with rubber gloves.

CONTACT DETAILS

Toll free Technical helpline 0800 008 008

Johannesburg: (011) 316 3133 • Cape Town (021) 386 1810 • Durban (031) 700 1535

TAL reserves the right to change the information on this datasheet.

Another successful installation guaranteed