



Norcros SA: TAL Marblefix

TAL MARBLEFIX®



- ❖ [Go to Specifile](#)
- ❖ [Click here to view supplier details](#)
- ❖ [See full brochure](#)

DESCRIPTION

TAL MARBLEFIX is a light coloured rapid setting, high strength, low shrinkage, and cement based powder adhesive for fixing tiles to walls and floors. It is especially suited for the fixing of marble and other light coloured tiles, and can also be used for the fixing of mosaics. It is also recommended for use with vitrified tiles. The adhesive was designed for easy use, allowing a full 1 1/2 hours pot life. TAL MARBLEFIX may be used in interior and exterior conditions. (Exterior conditions require the use of TAL BOND instead of water). TAL MARBLEFIX can be mixed with either clean water or used with TAL BOND for special applications. Using a notched TAL FLOOR TROWEL (which will give a solid bed of adhesive 3 - 4mm thick) 20kg will cover approximately 4m². Using a notched TAL WALL TROWEL (which will give a ribbed cover with ± 60% coverage ± 3mm thick) 20kg will cover approximately 7m².

TECHNICAL DATA

	With Water	With TAL BOND
Mix ratio	4 : 1	4 : 1
Pot Life	90 minutes	90 minutes
Open Times	15 minutes	15 minutes
Application Temperature Range	+ 5°C to + 30°C	+ 5°C to + 30°C
Grouting After	3 - 4 hours	3 - 4 hours
Full Service	6 - 8 hours	6 - 8 hours
Flexibility	Poor	Good
Temperature Resistance	0°C to + 100°C	- 30°C to + 100°C
Ageing	Excellent	Excellent
Resistance to Damp	Good	Excellent
Tensile Strength (24 Hours)	> 0.5N/mm ²	> 1.0N/mm ²

STORAGE AND SHELF LIFE

When stored in dry conditions, under cover between 5°C and 30°C, the product has a shelf life of 6 months.

PACKAGING

20kg and 5kg bags.

WARNING

DO NOT INGEST • USE ONLY AS DIRECTED • WEAR PROTECTIVE GLOVES AND GOGGLES • USE A SUITABLE DUST MASK.
• WORK IN A WELL VENTILATED AREA.

TAL GUARANTEE

TAL products are manufactured to the highest standards and are guaranteed to be free from manufacturing defects and fit for design purpose. TAL products must be used strictly in accordance with TAL's methods and materials specifications and good working practice.



DESCRIPTION

TAL MARBLEFIX is a light coloured rapid setting, high strength, low shrinkage, and cement based powder adhesive for fixing tiles to walls and floors. It is especially suited for the fixing of marble and other light coloured tiles, and can also be used for the fixing of mosaics. It is also recommended for use with vitrified tiles. The adhesive was designed for easy use, allowing a full 1 1/2 hours pot life. TAL MARBLEFIX may be used in interior and exterior conditions. (Exterior conditions require the use of TAL Bond instead of water). TAL MARBLEFIX can be mixed with either clean water or used with TAL BOND for special applications. Using a notched TAL FLOOR TROWEL (which will give a solid bed of adhesive 3 - 4mm thick) 20kg will cover approximately 4m². Using a notched TAL WALL TROWEL (which will give a ribbed cover with ± 60% coverage ± 3mm thick) 20kg will cover approximately 7m².

TECHNICAL DATA

	With Water	With TAL BOND
Mix ratio	4 : 1	4 : 1
Pot Life	90 minutes	90 minutes
Open Times	15 minutes	15 minutes
Application Temperature Range	+ 5°C to + 30°C	+ 5°C to + 30°C
Grouting After	3 - 4 hours	3 - 4 hours
Full Service	6 - 8 hours	6 - 8 hours
Flexibility	Poor	Good
Temperature Resistance	0°C to + 100°C	- 30°C to + 100°C
Ageing	Excellent	Excellent
Resistance to Damp	Good	Excellent
Tensile Strength (24 Hours)	> 0.5N/mm ²	> 1.0N/mm ²

STORAGE AND SHELF LIFE

When stored in dry conditions, under cover between 5°C and 30°C, the product has a shelf life of 6 months.

PACKAGING

20kg and 5kg bags.

WARNING

DO NOT INGEST • USE ONLY AS DIRECTED • WEAR PROTECTIVE GLOVES AND GOGGLES • USE A SUITABLE DUST MASK.
• WORK IN A WELL VENTILATED AREA.

TAL GUARANTEE

TAL products are manufactured to the highest standards and are guaranteed to be free from manufacturing defects and fit for design purpose. TAL products must be used strictly in accordance with TAL's methods and materials specifications and good working practice.



1 Add 20kg Marblefix to 5l clean, cool water.



2 Mix well while adding powder.



3 Apply adhesive.



4 Bed tiles or mosaic sheets.



5 Grout after 4 hours.



6 Clean off excess grout.

Another successful installation guaranteed

A **NORCROS** COMPANY



TAL MARBLEFIX[®]

TAL TECHNICAL ADVISORY SERVICE

For a detailed methods and materials specification contact the TAL TECHNICAL ADVICE CENTRE on our toll free line on 0800 008 008 or fax (011) 316 3127.

PRECAUTIONS

TAL MARBLEFIX is non-flammable and is not hazardous to health. Sensitive skin should be protected with rubber gloves.

CONTACT DETAILS

Toll free Technical helpline 0800 008 008

Johannesburg: (011) 316 3133 • Cape Town (021) 386 1810 • Durban (031) 700 1535

TAL reserves the right to change the information on this datasheet.

Another successful installation guaranteed