



Norcros SA: TAL Mortar seal

- ❖ [Go to Specifile](#)
- ❖ [Click here to view supplier details](#)
- ❖ [See full brochure](#)

TAL MORTAR SEAL

DESCRIPTION

TAL MORTAR SEAL is a one part, penetrating sealer specially designed for sealing and protecting wall and floor grouts, for both internal and external applications. It is also suitable for sealing of bricks and concrete, also terracotta, terrazzo, quarry and slate tiles.

FEATURES

- Reduces efflorescence, grout staining, and provides an easy cleaning surface.
- Dries to a clear matt finish which should not change the colour of the mortar.
- One part system, thus easy handling.
- UV stable, thus can be used both internally and externally

NB: TAL MORTAR SEAL does not totally seal the grouts against oil or fatty stains. It does facilitate cleaning, as long as it is done immediately after spillage.

Due to the diversity of its application, it is imperative that TAL MORTAR SEAL be tested for suitability before use.

PREPARATION

The surface to be sealed should be clean, dust-free and dry. All dirt, grease or old coatings must be completely removed before application. Grouts should be treated after at least 48 hrs from application. Tiles should preferably be treated as soon after laying as possible, and before the appearance of efflorescence.

APPLICATION

Ensure all surfaces are clean and dry before sealing. TAL MORTAR SEAL can be applied by brush or roller or spraying. Two brush coats of sealer applied before complete drying of previous should normally be adequate. Although coverage will depend on the absorbcency of the surface, 1L of MORTAR SEAL should cover 8 – 10 m². The coated surface should not be subjected to use for 12 hours, and the full effect of the sealer develops between 24 hours and 7 days.

CLEANING

TAL Cleaning Solvent should be used for cleaning brushes.

MAINTENANCE

Clean by damp or wet mopping using a mild household detergent when required. Always wipe up heavy spills immediately. Heavy, persistent stains can be removed with the aid of a solvent such as thinners. A further coat of TAL MORTAR SEAL may be required thereafter. Yearly re-coats are advisable.

HEALTH AND SAFETY

- TAL MORTAR SEAL contains flammable liquids. Avoid naked flames and use only in well ventilated areas.
- Do not ingest.

PACKAGING

Available in 5 litres metal tins.

STORAGE AND SHELF LIFE

TAL MORTAR SEAL should be stored in dry conditions away from direct sunlight. Under recommended storage conditions TAL MORTAR SEAL has a shelf life of 6 months from date of manufacture.

TAL MORTAR SEAL

DESCRIPTION

TAL MORTAR SEAL is a one part, penetrating sealer specially designed for sealing and protecting wall and floor grouts , for both internal and external applications.

It is also suitable for sealing of bricks and concrete, also terracotta, terrazzo, quarry and slate tiles.

FEATURES

- Reduces efflorescence, grout staining, and provides an easy cleaning surface.
- Dries to a clear matt finish which should not change the colour of the mortar.
- One part system, thus easy handling.
- UV stable, thus can be used both internally and externally

NB : TAL MORTAR SEAL does not totally seal the grouts against oil or fatty stains. It does facilitate cleaning, as long as it is done immediately after spillage.

Due to the diversity of its application, it is imperative that TAL MORTAR SEAL be tested for suitability before use.

PREPARATION

The surface to be sealed should be clean, dust-free and dry. All dirt, grease or old coatings must be completely removed before application. Grouts should be treated after at least 48 hrs from application. Tiles should preferably be treated as soon after laying as possible, and before the appearance of efflorescence.

APPLICATION

Ensure all surfaces are clean and dry before sealing. TAL MORTAR SEAL can be applied by brush or roller or spraying. Two brush coats of sealer applied before complete drying of previous should normally be adequate. Although coverage will depend on the absorbency of the surface, 1L of MORTAR SEAL should cover 8 – 10 m². The coated surface should not be subjected to use for 12 hours, and the full effect of the sealer develops between 24 hours and 7 days.

CLEANING

TAL Cleaning Solvent should be used for cleaning brushes.

MAINTENANCE

Clean by damp or wet mopping using a mild household detergent when required. Always wipe up heavy spills immediately. Heavy, persistent stains can be removed with the aid of a solvent such as thinners. A further coat of TAL MORTAR SEAL may be required thereafter. Yearly re-coats are advisable.

HEALTH AND SAFETY

- TAL MORTAR SEAL contains flammable liquids. Avoid naked flames and use only in well ventilated areas.
- Do not ingest.

PACKAGING

Available in 5 litres metal tins.

STORAGE AND SHELF LIFE

TAL MORTAR SEAL should be stored in dry conditions away from direct sunlight. Under recommended storage conditions TAL MORTAR SEAL has a shelf life of 6 months from date of manufacture.