



### Norcros SA: TAL Mosaicfix

## TAL MOSAICFIX®



- ❖ [Go to Specifile](#)
- ❖ [Click here to view supplier details](#)
- ❖ [See full brochure](#)

#### DESCRIPTION

TAL MOSAICFIX is a white powder adhesive for fixing mosaics onto walls and floors. It can also be used as a grouting or pre-grouting of mosaics. TAL MOSAICFIX can be mixed with either clean water or used with TAL BOND for special applications. Provided the correct method of application is used, approximately 4kg of TAL MOSAICFIX should cover one square metre, the thickness being 3mm, inclusive of adhesive/grouting combination.

#### TECHNICAL DATA

	With Water	With TAL Bond
Mix ratio	2.85 : 1	2.85 : 1
Pot Life	min 3 hours	min 3 hours
Open Times	20 minutes	20 minutes
Application Temperature Range	+ 5°C to + 30°C	+ 5°C to + 30°C
Grouting After	24 hours	24 hours
Full Service	48 hours	48 hours
Flexibility	Floor	Good
Ageing	Excellent	Excellent
Resistance to Damp	Good	Excellent
Tensile Strength (Standard Conditions)	> 0.5N/mm <sup>2</sup>	> 1.0N/mm <sup>2</sup>

#### STORAGE AND SHELF LIFE

When stored under cover between 5°C and 30°C, the product has a shelf life of 6 months. Never store directly on a concrete floor. Protect from damp.

#### PACKAGING

20kg and 5kg bags

#### WARNING

DO NOT INGEST • USE ONLY AS DIRECTED • WEAR PROTECTIVE GLOVES AND GOGGLES • USE A SUITABLE DUST MASK. • WORK IN A WELL VENTILATED AREA.

Solutions Through Technology



Another successful installation guaranteed



## DESCRIPTION

TAL MOSAICFIX is a white powder adhesive for fixing mosaics onto walls and floors. It can also be used as a grouting or pre-grouting of mosaics. TAL MOSAICFIX can be mixed with either clean water or used with TAL BOND for special applications. Provided the correct method of application is used, approximately 4kg of TAL MOSAIC FIX should cover one square metre, the thickness being 3mm, inclusive of adhesive/grouting combination.

## TECHNICAL DATA

	With Water	With TAL Bond
Mix ratio	2.85 : 1	2.85 : 1
Pot Life	min 3 hours	min 3 hours
Open Times	20 minutes	20 minutes
Application Temperature Range	+ 5°C to + 30°C	+ 5°C to + 30°C
Grouting After	24 hours	24 hours
Full Service	48 hours	48 hours
Flexibility	Poor	Good
Ageing	Excellent	Excellent
Resistance to Damp	Good	Excellent
Tensile Strength (Standard Conditions)	> 0.5N/mm <sup>2</sup>	> 1.0N/mm <sup>2</sup>

## STORAGE AND SHELF LIFE

When stored under cover between 5°C and 30°C, the product has a shelf life of 6 months. Never store directly on a concrete floor. Protect from damp.

## PACKAGING

20kg and 5kg bags

## WARNING

DO NOT INGEST • USE ONLY AS DIRECTED • WEAR PROTECTIVE GLOVES AND GOGGLES • USE A SUITABLE DUST MASK.  
• WORK IN A WELL VENTILATED AREA.



1 Add 5kg Mosaicfix to 1.75 litres clean, cool water



2 Mix well while adding powder.



3 Apply adhesive



4 Pre-grout mosaic sheets



5 Bed mosaics



6 Clean off excess grout

Another successful installation guaranteed

A NORCHOS COMPANY



# TAL MOSAICFIX®

## TAL GUARANTEE

TAL products are manufactured to the highest standards and are guaranteed to be free from manufacturing defects and fit for design purpose. TAL products must be used strictly in accordance with TAL's methods and materials specifications and good working practice.

## TAL TECHNICAL ADVISORY SERVICE

For a detailed methods and materials specification contact the TAL TECHNICAL ADVICE CENTRE on our toll free line on 0800 008 008 or fax (011) 316 3127.

## PRECAUTIONS

TAL MOSAICFIX is non-flammable. Sensitive skin should be protected with rubber gloves.

## CONTACT DETAILS

Toll free Technical helpline 0800 008 008

Johannesburg: (011) 316 3133 • Cape Town (021) 386 1810 • Durban (031) 700 1535

TAL reserves the right to change the information on this datasheet.

**Another successful installation guaranteed**