

Norcros SA: TAL Pro-tac

- Go to Specifile on-line
- Search Specifile
- [Click here to view supplier details](#)
- See full brochure

TAL PRO-TAC®



DESCRIPTION

TAL PRO-TAC is a solvent free, modified acrylic based adhesive, suitable for the installation of carpets and carpet tiles where repositionability or removability is important.

AREAS OF APPLICATION

TAL PRO-TAC is suitable for installing carpets and carpet tiles in applications where subsequent ease of removal of the carpeting is important. TAL PRO-TAC is suitable for application onto concrete, slate, wood and metal access flooring. TAL PRO-TAC is NOT suitable for adhering carpeting that has been coated with a rubber or bitumen based wear-under layer.

SURFACE PREPARATION

The surface must be structurally sound, clean and dry and free from shutter release and curing agents, latices and surface contamination such as dust, dirt, waxes, oils, old adhesives, paint, grease, sealants, weak cement screeds and render, etc. Bituminous compounds must be removed completely. New concrete or screeds must be at least 28 days old, and new renders or brickwork must be at least 14 days old. The floor must be completely smooth and level. Rough surfaces can be levelled using TAL RAMPOLK. Very porous surfaces must be primed with TAL FLOORPRIMER, which must be left to dry before applying TAL PRO-TAC.

APPLICATION

Stir well before use. TAL PRO-TAC can be applied using one of the two following methods:

Concrete, Slate, Wood:

- Serrated trowel with triangular notches of 1.5mm x 1.5mm with 4mm centres (concrete, wood)
- New lambswool paint roller

Metal Access Flooring:

- New mohair paint roller

Apply the adhesive onto the clean substrate and allow to dry completely (preferably overnight if a serrated trowel was used) before installing the floor covering.

TECHNICAL DATA

Type	Modified Solvent free Acrylic Adhesive
Colour	Yellow
Flash Off Time	± 30 Minutes
Open Time	Permanently tacky in dust-free areas
Solids Content	50 ± 2%
Viscosity (Brookfield)	8 000 – 12 000 cP (RYT 6/20/25°C)
Specific Gravity	0.96 ± 0.02
pH	7 – 9
T Application Range	10°C – 30°C
Coverage	± 6 – 7m ² /l
Cleaning	Water when wet Solvent when dry



Another successful installation guaranteed



A NORCROS COMPANY

Solutions Through Technology

Specifile - Architectural Information Service - the source of South African building products and suppliers

DESCRIPTION

TAL PRO-TAC is a solvent free, modified acrylic based adhesive, suitable for the installation of carpets and carpet tiles where repositionability or removability is important.

AREAS OF APPLICATION

TAL PRO-TAC is suitable for installing carpets and carpet tiles in applications where subsequent ease of removal of the carpeting is important. TAL PRO-TAC is suitable for application onto concrete, slate, wood and metal access flooring. TAL PRO-TAC is NOT suitable for adhering carpeting that has been coated with a rubber or bitumen based wear-under layment.

SURFACE PREPARATION

The surface must be structurally sound, clean and dry and free from shutter release and curing agents, laitance and surface contamination such as dust, dirt, waxes, oils, old adhesives, paint, grease, sealants, weak cement screeds and renders, etc. Bituminous compounds must be removed completely. New concrete or screeds must be at least 28 days old, and new renders or brickwork must be at least 14 days old. The floor must be completely smooth and level. Rough surfaces can be levelled using TAL RAPIDFIX. Very porous surfaces must be primed with TAL FLOOR PRIMER, which must be left to dry before applying TAL PRO-TAC.

APPLICATION

Stir well before use. TAL PRO-TAC can be applied using one of the two following methods :

Concrete, Slate, Wood:

- Serrated trowel with triangular notches of 1.5mm x 1.5mm with 4mm centres (concrete, wood)
- New lambswool paint roller

Metal Access Flooring:

- New mohair paint roller

Apply the adhesive onto the clean substrate and allow to dry completely (preferably overnight if a serrated trowel was used) before installing the floor covering.

TECHNICAL DATA

Type	Modified Solvent free Acrylic Adhesive
Colour	Yellow
Flash Off Time	± 30 Minutes
Open Time	Permanently tacky in dust-free areas
Solids Content	50 ± 2%
Viscosity (Brookfield)	8 000 – 12 000 cPs (RVT 6/20/25°C)
Specific Gravity	0.96 ± 0.02
pH	7 – 9
T° Application Range	10°C - 30°C
Coverage	± 6 – 7m ² /ℓ
Cleaning	Water when wet Solvent when dry



TECHNICAL ADVICE CENTRE NATIONWIDE 0860 000 TAL(825)

Another successful installation guaranteed



A NORCROS COMPANY

TAL PRO-TAC®

PACKAGING

TAL PRO-TAC is available in 20ℓ plastic containers, suitable for rail and road delivery.

STORAGE & SHELF LIFE

When stored in dry internal conditions between 5°C and 30°C and out of direct sunlight the product has a shelf life of 6 months from date of manufacture. Never store directly on a concrete floor.

WARNING

DO NOT INGEST. USE ONLY AS DIRECTED. PROTECT SENSITIVE SKIN WITH RUBBER GLOVES

TAL GUARANTEE

TAL products are manufactured and tested to TAL procedures, which are maintained in accordance with Quality System Standard ISO 9001 : 2000. TAL products are guaranteed to be free from manufacturing defects and fit for design purposes. TAL guarantees the performance of its products when used strictly in accordance with TAL's materials and methods specifications and good working practice.

TAL TECHNICAL ADVICE CENTRE

For a detailed Materials and Methods Specification contact the TAL Technical Advice Centre on 0860 000 TAL(825), or e-mail taltech@norcrossa.com. Branches : Johannesburg (011)316-3133; Cape (021) 386-1810; Natal (031) 700-1535

PRECAUTIONS

Contact TAL (Pty) Ltd for further health and safety information. Dispose of this product in accordance with local regulations.

IMPORTANT NOTICE

TAL believes the information on this sheet to be correct – but does not guarantee its accuracy or completeness. Conduct your own tests of this product to determine its suitability for intended use. User assumes all risks and liability during testing and use of this product. The only obligation of TAL shall be to replace any of this product proved to be defective in material. TAL shall not be liable for any injury, loss or damage, direct or consequential, relating to the use or inability to use this product. Except as expressly provided above, all products sold and samples furnished without any warranty of merchantability or any other warranty, express or implied. TAL (Pty) Ltd reserves the right to change the information on this datasheet.

Another successful installation guaranteed

