

Norcros SA: TAL Quarrygrout

- Go to Specifile on-line
- Search Specifile
- [Click here to view supplier details](#)
- [See full brochure](#)

Specifile - Architectural Information Service - the source of
South African building products and suppliers

TAL QUARRYGROUT®



DESCRIPTION
TAL QUARRYGROUTS are suitable for filling ceramic tile joints up to a width of 25mm. Available in a variety of colours, they are designed to inhibit moisture ingress and prevent bacterial and fungal growth. They are not suitable for use with soft glazed wall tiles.

DIRECTIONS
Surface preparation
Grouting must not commence until the adhesive beneath the tiles has set sufficiently. Refer to the adhesive instructions. Seal unglazed tiles with TAL INVISSEAL before grouting to prevent staining. The tiles must be clean, dry and free of dust, and the joints must have been raked out and cleaned before grouting.

Mixing
Add 20kg TAL QUARRYGROUT to 5 litres clean water. Mix well to a creamy consistency. Let the mix stand for a few minutes before stirring again. Use within 30 minutes. For permanently wet conditions, heavy traffic areas, external situations, or where some flexibility is required, replace the water in the mix with TAL BOND.

Application
Apply the mix to the surface and rub the grout well into the tile joints using a TAL GROUT SQUEEGE, making sure that the joints are filled properly. Wipe off excess grout and smooth the surface of the grout with the squeegee. Allow the grout to harden sufficiently to prevent accidental removal from the joints, and clean off any grout remaining on the face of the tiles with a damp TAL SPONGE, rinsing frequently in clean water. Allow the tiles to dry and polish with a clean, dry cloth. Exterior installations should be protected from inclement weather conditions by covering with plastic sheeting until grout has hardened fully. Clean tools before grout hardens.

ALWAYS CHECK THAT THE GROUT DOES NOT STAIN THE TILES BEFORE USING.

When TAL QUARRYGROUT has been added to the mix, it is imperative that all traces of grout are removed from the face of the tiles before it hardens.

COVERAGE
This bag will cover a 14m² for tile joints 10mm wide and 10mm deep.

STORAGE AND SHELF LIFE
When stored under cover between 5°C and 30°C, the product has a shelf life of 6 months. Never store directly on a concrete base. Protect from damp.

PACKAGING
TAL QUARRYGROUT is available in 5kg and 20kg bags, depending on colour chosen.

WARNING
DO NOT INGEST • USE ONLY AS DIRECTED • WEAR PROTECTIVE GLOVES AND GOGGLES • USE A SUITABLE DUST MASK • WORK IN A WELL VENTILATED AREA.

TAL GUARANTEE
TAL products are manufactured to the highest standards and are guaranteed to be free from manufacturing defects and fit for design purpose. TAL products must be used strictly in accordance with TAL's methods and materials specifications and good working practice.

Solutions Through Technology





Add 20kg
Quarrygrout to
5 litres, 10%
water



Mix well and use
within 30 mins



Rub grout



Clean off excess
grout

Another successful installation guaranteed


a **STANTAM** COMPANY

TAL QUARRYGROUT®



DESCRIPTION

TAL QUARRYGROUTS are suitable for filling ceramic tile joints up to a width of 25mm. Available in a variety of colours, they are designed to inhibit moisture ingress and prevent bacterial and fungal growth. They are not suitable for use with soft glazed wall tiles.

DIRECTIONS

Surface preparation

Grouting must not commence until the adhesive beneath the tiles has set sufficiently. Refer to the adhesive instructions. Seal unglazed tiles with TAL INVISISEAL before grouting to prevent staining. The tiles must be clean, dry and free of dust, and the joints must have been raked out and cleaned before grouting.

Mixing

Add 20kg TAL QUARRYGROUT to 5 litres clean water. Mix well to a creamy consistency. Let the mix stand for a few minutes before stirring again. Use within 30 minutes. For permanently wet conditions, heavy traffic areas, external situations, or where some flexibility is required, replace the water in the mix with TAL BOND.

Application

Apply the mix to the surface and rub the grout well into the tile joints using a TAL GROUT SQUEEGEE, making sure that the joints are filled properly. Wipe off excess grout and smooth the surface of the grout with the squeegee. Allow the grout to harden sufficiently to prevent accidental removal from the joints, and clean off any grout remaining on the face of the tiles with a damp TAL SPONGE, rinsing frequently in clean water. Allow the tiles to dry and polish with a clean, dry cloth. Exterior installations should be protected from inclement weather conditions by covering with plastic sheeting until grout has hardened fully. Clean tools before grout hardens.

ALWAYS CHECK THAT THE GROUT DOES NOT STAIN THE TILES BEFORE USING.

When TAL QUARRYGROUT has been added to the mix, it is imperative that all traces of grout are removed from the face of the tiles before it hardens.

COVERAGE

This bag will cover $\pm 14\text{m}^2$ for tile joints 10mm wide and 10mm deep.

STORAGE AND SHELF LIFE

When stored under cover between 5°C and 30°C, the product has a shelf life of 6 months. Never store directly on a concrete floor. Protect from damp.

PACKAGING

TAL QUARRYGROUT is available in 5kg and 20kg bags, depending on colour chosen.

WARNING

DO NOT INGEST • USE ONLY AS DIRECTED • WEAR PROTECTIVE GLOVES AND GOGGLES • USE A SUITABLE DUST MASK.
• WORK IN A WELL VENTILATED AREA.

TAL GUARANTEE

TAL products are manufactured to the highest standards and are guaranteed to be free from manufacturing defects and fit for design purpose. TAL products must be used strictly in accordance with TAL's methods and materials specifications and good working practice.



1 Add 20kg Quarrygrout to 5L clean, cool water.



2 Mix well and use within 30 min.



3 Apply grout



4 Clean off excess grout.

Another successful installation guaranteed

A NORCROS COMPANY



Solutions Through Technology

TAL QUARRYGROUT®

TAL TECHNICAL ADVISORY SERVICE

For a detailed methods and materials specification contact the TAL TECHNICAL ADVICE CENTRE on our toll free line on 0800 008 008 or fax (011) 316 3127.

CONTACT DETAILS

Toll free Technical helpline 0800 008 008

Johannesburg: (011) 316 3133 • Cape Town (021) 386 1810 • Durban (031) 700 1535

TAL reserves the right to change the information on this datasheet.

Another successful installation guaranteed