

# CreteCare Floor Polish Stripper Datasheet

Aug 2019

Page 1 of 2

Acrylic floor polish stripper / remover / cleaner of most acrylic polymer floor dressing polishes on the market.

## Technical Data

Physical state	Liquid
Appearance	Light blue
Specific gravity (density)	1.04 - 1.6g/cm <sup>3</sup> at 20°C
Solubility	Soluble in water
pH	± 12
Odour	Typical
Boiling point	100°C
Coverage	5m <sup>2</sup> / litre

## Purpose

**CreteCare Floor Polish Stripper** is a powerful cleaning and acrylic polymer floor polish stripping medium. It contains a selection of non-ionic and anionic surfactants and glycol ethers as well as proprietary preservatives to extend the product's shelf life.

## Applications

- Applied as a cleaner / stripper on all surfaces where an acrylic polymer type floor polish has been applied.
- Highly active - the reaction takes place immediately in order to save time and cut down on labour costs.

## Dilution process before use

Dilute UP TO 1:5 with water (1 part **CreteCare Floor Polish Stripper** with 5 parts water); depending on the coating thickness and type of polymer. Test for suitable dilution in an inconspicuous area before use.

## Masking

For best results all windows, doors and adjacent surfaces should be masked using painters masking tape (blue) and brown paper. All masking material must be removed at the end of the day's work.

## Application

Spread over the surface as needed and leave for a few minutes. Scrub and rinse well with clean water. Repeat this process where necessary. Use of a blue stripping pad will improve stripping efficiency.

## Shelf Life & Storage

Store between 10°C to 38°C. Use within 12 months of purchase.

## Packaging

Available in 1 litre containers.

## Safety Precautions

Can cause burns and irritation to respiratory system. In case of contact with eyes, rinse immediately with water and seek medical advice. Wear suitable protective equipment.

Cemcrete provides a comprehensive technical service based on over 4 decades of experience in the field of surface applications and cement technology. Cemcrete believes, to the best of its knowledge, that the information contained herein is true and accurate at the date of issuance and is subject to change without prior notice. For further clarification of these instructions, contact Cemcrete.



# CreteCare Floor Polish Stripper Datasheet

Aug 2019

Page 2 of 2

## Manufacturer's Warranty

---

Cemcrete warrants that the products manufactured by it shall be free from material defects and will be consistent with its normal high quality. Should any of the products be proven defective, the liability to Cemcrete shall be limited to replacement of the product ex-factory. Cemcrete makes no warranty as to merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties expressed or implied. The user shall determine the suitability of the product for his intended use and assume all risks and liability in connection therewith.

Cemcrete provides a comprehensive technical service based on over 4 decades of experience in the field of surface applications and cement technology. Cemcrete believes, to the best of its knowledge, that the information contained herein is true and accurate at the date of issuance and is subject to change without prior notice. For further clarification of these instructions, contact Cemcrete.

---

### Johannesburg Head Office

8 Telford Street  
Industria  
011 474 2415

### Johannesburg Showroom

227 Jan Smuts Avenue  
Parktown North  
011 447 3149

### Centurion Showroom & Warehouse

15 Coachmen's Park  
26 Jakaranda Street, Centurion  
012 653 6808

### Cape Town Showroom & Warehouse

Eagle Park, cnr Bosmansdam &  
Omuramba Roads, Montague Gardens  
021 555 1034