

Imprint Mat Tool Datasheet

January 2019

Page 1 of 1

Description

Mat imprinting tools for imparting texture and patterns to freshly placed concrete, screeds, toppings and plasters. The surface to be printed must be plastic in order for the print to take effect.

Composition

These mats are made from a fixed ratio polyether based Polyurethane system that produces elastomers of various shore hardiness's.

General

- · Cemcrete's imprinting mats are used to transform the above surfaces into patterns and finishes that mimic other building patterns and features.
- · By combining the structural and wear resistance of cement with the look of other materials, they create natural appearing, textures and low maintenance surfaces in a wide variety of patterns.
- · Cemcrete's imprint mats can be used in conjunction with Cemcrete products such as Colour Hardener dry shake powder, DecoCrete and CemPlaster.
- · Cemcrete also supplies Coloured release agent in numerous colours to facilitate the release of the mats from the surface as well as to add additional colour to the base colour.

Storage

- · Mats must be properly cleaned and stored after use. Store flat and face up to prevent deformation. Do store in direct sunlight. Covering with opague plastic is recommended.
- The lifespan of the mat is determined by the amount of use, how it is used and stored.

Types

Please consult the Cemcrete's imprint mat brochure for the various mats available.

Application procedure

Please consult Cemcrete's technical department for imprinting procedures.

Cemcrete provides a comprehensive technical service based on over 4 decades of experience in the field of surface applications and cement technology. Cemcrete believes, to the best of its knowledge, that the information contained herein is true and accurate at the date of issuance and is subject to change without prior notice. For further clarification of these instructions, contact Cemcrete.